HAND WIND REELS

Steel rod frame and handle with wide base. Heavy gauge steel flanges. No collector rings, brushes or slip rings. Large rewinding knob. Available with or without receptacles, spring loaded flip lids, or a lead cord. Capable of storing up to 150 ft. of 12/3 or 200 ft. of 14/3 SOW cord. Disconnecting electrical device is required to wind or unwind the cable. Reels with cord have plug on free end of cable (except for 915 series).

910/911/916 SERIES CABLE REEL



Cable Reels with Receptacles

Features four receptacles and a plug on free end of cable. Available with GFCI protection.

RECEPTACLE	RECEPTACLE		NUMBER OF	GFCI	PART NO.		
RATING	CONFIGURATION		RECEPTACLES	PROTECTION	WITHOUT CABLE	WITH 12/3 SOW	WITH 14/3 SOW
15A 125V	NEMA 5-15	(h)(h)	4	NO	910	910_1231	910_143²
15A 125V	NEMA L5-15	@ @	4	NO	911	911_1231	911_143 ²
15A 125V	NEMA 5-15	(1) (1)	4	YES	916	916_1231	916_143 ²

Cable Reels with Covered Receptacles

Features two receptacles with weather resistant, spring-loaded flip lids and a plug on free end of cable (920 series does not include receptacles).

RECEPTACLE	RECEPTACLE		NUMBER OF	GFCI	PART NO.		
RATING	CONFIGURATIO	N	RECEPTACLES	PROTECTION	WITHOUT CABLE	WITH 12/3 SOW	WITH 14/3 SOW
20A 250V	NEMA L2-20	٥٥	2	NO	912	912_1221	912_142²
20A 125V/250V	NON-NEMA LOCKING	00	2	NO	913	913_1231	913_143 ²
20A 125V	NEMA L5-20	٩	2	NO	914	914_1231	914_143 ²
_	_		NONE	NO	920	920 1231	920 143 ²

Cable Reels with Lead Cord, Plug, and Connector - No Receptacles

RECEPTACLE	RECEPTACLE	NUMBER OF	GFCI	PART NO.		
RATING	CONFIGURATION	RECEPTACLES	PROTECTION	WITHOUT CABLE	WITH 12/3 SOW	WITH 14/3 SOW
_	_	NONE	NO	915	915_1231	915_143²

¹ CABLE REELS WITH 12/3 SOW ONLY AVAILABLE WITH 100 FT. AND 150 FT. OF CABLE. USE MATRIX BELOW.

Cable Length: To select the length of primary cable for the outlet box, place one of the following letters in the space.





MOST WOODHEAD PRODUCTS HAVE U.L. AND/OR CSA APPROVALS. FOR A LISTING OF APPROVALS BY PART NUMBER, SEE PAGES 262-269.

² CABLE REELS WITH 14/3 SOW AVAILABLE WITH 100 FT., 150 FT. AND 200 FT. OF CABLE. USE MATRIX BELOW.